



19

JAPANESE PATENT OFFICE

## PATENT ABSTRACTS OF JAPAN

(11) Publication number:

(43) Date of publication of application: 29.03.1994

06090409 A

H04N 5/44 (51) Int. CI H04N 5/80

04266635 (21) Application number:

08.09.1992 (22) Date of filing: (54) TELEVISION RECEPTION CIRCUIT

(57) Abstract:


BEST AVAILABLE COPY

PURPOSE: To provide the television reception circuit which outputs a sound signal after such correction that the high frequency component of the sound signal is reduced in the case of the weak electric field reception CONSTITUTION: In a range correction block 18, a sistor TR Q3 when judging it by detection information inputted to a detection information input terminal that the PLL lock state is not released, and the block 21 out-When the 'Low' signal is outputted, a TR Q1 is turned on by an input sound signal, and the sound signal is outputted from a sound output terminal through the tone control block 21 outputs a 'Low' signal to a tranputs a 'Hi' signal to the TR Q3 when judging it by deemitter electrode of the TR C1 and an output resistection information that the PLL lock state is released.

(71) Applicant: CASIO COMPUT CO LTD

SUMI HIDETOSHI (72) Inventor: sound signal, and the sound signal is outputted to a sound amplifier through the sound output terminal

COPYRIGHT: (C)1994, JPO& Japio



file:///C|/Documents%20and%20Settings/deeptid/Desktop/DEEPTI---20050817--20/dwi/JP06090409A2.htm (1 of 2) [8/18/2005 5:22:05 PM]

tance HO; and when the 'Hi' signal is outputted, the TR O3 is turned on, and the signal pass band characteristic is changed by the connection capacity in the TH Q3 to reduce the high frequency component of the

100 Cig

BEST AVAILABLE COPY

**/**\_\_\_

file:///C|/Documents%20and%20Settings/deeptid/Desktop/DEEPTI---20050817--20/dw//JP06090409A2.htm (2 of 2) [8/18/2005 5:22:05 PM]